

Angle Drill LXT®

DDA351RTJ

18V • 13,5 Nm • 0 - 1 800 min⁻¹

Angle drill with keyless chuck for tight spaces

An angle drill with an 89 mm head for access to tight spaces. With a max. torque of 13.5Nm. The tool's chuck capacity is 1.5-10 mm. Two 5.0 Ah batteries and charger in a Makpac case.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1800 min ⁻¹
Max. fastening torque Hard/Soft	- / 13,5 Nm
Max. Drilling Diameter in Wood	25 mm
Max. Drilling Diameter in Steel	10 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 10 mm
Sound Pressure Level (L _{pA})	70 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Drilling	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Product net weight	1,1 kg
Tool weight with battery (EPTA)	1,6 - 1,9 kg
Product Dimensions (L x W x H):	326 x 79 x 115 mm

User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381816731

Link to product - www.makita.com



Related products

■ Standard AC

153489-2
Grip complete 125 mm



821550-0
Makpac case (2)



■ Standard MA

BL1850B (2x)
Battery LXT® 5,0 Ah



DC18RC
Battery Charger LXT®



■ Optional AC

153489-2
Grip complete 125 mm



450128-8
Battery cover, LXT®, 14,4 – 18V



821550-0
Makpac case (2)



838040-6
Inner Tray for Makpac (2)



■ Other

[User manual](#)

[Parts drawing](#)