

Angle Grinder LXT®

DGA513RTJ

18V • 125 mm • 3 000 – 8 500 min⁻¹

Efficient brushless tool with adjustable speed

A small, brushless angle grinder with a 125 mm wheel for demanding professional use. Constant speed electronics, overload protection and AVT anti-vibration side grip and adjustable speed control. Two 5.0Ah batteries and a rapid charger in a Makpac case.



18V **BL** MOTOR **ADT AFT** (BRAKE)

Technical specifications

Brushless Motor	✓
Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	3000 - 8500 min ⁻¹
Max. Depth of Cut	29 mm
Bore Size (Arbor Diameter)	22,23 mm
Grinding Disc Diameter	125 mm
Anti-Restart Function (NVR Switch)	✓
Electronic brake	✓
Sound Pressure Level (L _{pA})	79 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	6,0 - 6,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	2,4 - 3,0 kg
Product Dimensions (L x W x H):	382 x 140 x 145 mm

User benefits

- Brushless maintenance-free and long-life motor
- Disc brake

EAN 0088381853620

Link to product - www.makitauk.com



Related products

Standard AC

A-80656

Grinding Wheel 125 X 6 Mm, Wa36N,



782423-1

Lock nut wrench 35



158237-4

Grip 36 complete



821551-8

Makpac case (3)



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

123145-8

Toolless wheel cover, 125 mm



195239-9

Dust cover attachment 125 mm, Ø 32



195354-9

Toolless Lock Nut M14, 180 - 230



196845-3

Dust collecting cover 125 mm, Ø



199710-5

Wheel Guard Cover 125 mm



450128-8

Battery cover, LXT®, 14,4 – 18V



821551-8

Makpac case (3)



839252-4

MakPac Type 3 Inlay



Other

User manual

Parts drawing