

Combi Drill LXT®

DHP486Z

18V • 130 Nm • 0 – 2 100 min⁻¹

A powerful, brushless general-use impact drill for screwdriving and drilling

An efficient, brushless drill for screwdriving and drilling with or without hammer action, two power settings. Max. torque of 130 / 65 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Tool only, battery and charger not included



Technical specifications

Brushless Motor	✓
Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 550 / 2100 min ⁻¹
Max. fastening torque Hard/Soft	130 / 65 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 8250 / 31 500 min ⁻¹
Max. Drilling Diameter in Wood	76 mm
Max. Drilling Diameter in Masonry	16 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	95 dB(A)
Sound Pressure Level (L _{pA})	84 dB(A)

User benefits

- Optimum handle design
- LED light illuminates the work site
- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Electronic overload protection protects the user and the device

EAN 0088381739566

Link to product - www.makita.uk.com



Related products

Standard AC

122576-8

Stopper Pole



251314-2 (2x)

Truss Head Screw M4*12, Td140D



346317-0

Belt Hook



452947-8

Bitholder



784637-8

Screw Bit, Ph2 – S6, 45 Mm, Double



Optional AC

122576-8

Stopper Pole



122D10-2

Grip Assembly



251314-2 (2x)

Truss Head Screw M4*12, Td140D



346317-0

Belt Hook



346449-3

Belt Hook



450128-8

Battery cover, LXT®, 14,4 – 18V



452947-8

Bitholder



784637-8

Screw Bit, Ph2 – S6, 45 Mm, Double



821550-0

Makpac case (2)



837916-4

MakPac (2) Inlay



D-72877

Drill bit set T.C.T, 5 pcs



Other

User manual

Parts drawing