

Rotary Hammer LXT®

DHR202RTJ

18V • SDS-Plus • 20 mm • 2.0 J

Professional three-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 1 100 min⁻¹. Impact energy of 2.0 J and max. drilling capacity of 20 mm in concrete. With two 5.0 Ah batteries and a charger.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	0 - 1100 min ⁻¹
Impacts per Minute (IPM)	0 - 4000 min ⁻¹
Max. Drilling Diameter in Wood	26 mm
Max. Drilling Diameter in Concrete	20 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	6 - 10 mm
Impact Energy	1,9 J
Sound Power Level (L _{WA})	99 dB(A)
Sound Pressure Level (L _{pA})	88 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Drilling	3 m/s ²
Vibration Level (3 axes), Impact Drilling	15,1 m/s ²

User benefits

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site
- Impact drilling, non-impact drilling and spike function
- Reversing switch
- Compact and ergonomic design
- Works with 18V Li-ion battery (not 1.3Ah battery)
- Easy blade setting system for fast blade installation

EAN 0088381692069

Link to product - www.makita.com



Related products

Standard AC

324219-0
Depth Gauge



450128-8
Battery cover, LXT®, 14,4 – 18V



821551-8
Makpac case (3)



Standard MA

BL1850B (2x)
Battery LXT® 5,0 Ah



DC18RC
Battery Charger LXT®



Optional AC

193472-7
Dust extraction set Ø 25 / 31 mm



324219-0
Depth Gauge



450128-8
Battery cover, LXT®, 14,4 – 18V



821551-8
Makpac case (3)



837634-4
MakPac (3) Inlay



Other

[User manual](#)

[Parts drawing](#)