



Reciprocating Saw LXT®

DJR186RTE

18V • 0 – 2 800 min⁻¹ • 32 mm

Efficient basic reciprocating saw

An efficient reciprocating saw for spark-free cutting of metal and demolition work. Stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment. Two 5.0 Ah batteries and a fast charger in a case.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	0 - 2800 min ⁻¹
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L _{WA})	95 dB(A)
Sound Pressure Level (L _{pA})	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	13,0 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	3,5 - 3,8 kg
Product Dimensions (L x W x H):	486 x 81 x 223 mm

User benefits

- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381806725

Link to product - www.makitauk.com



Related products

■ Standard AC

821620-5

Plastic Carrying Case



■ Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



■ Optional AC

821620-5

Plastic Carrying Case



B-05169

Reciprosaw Blade 152 x 0,9 mm



■ Other

User manual

Parts drawing