

Impact Driver LXT®

DTD153RTJ

18V • 1/4" • 170 Nm • 0 – 3 400 min⁻¹

Extra-compact brushless impact driver for quick driving

A compact and light brushless impact driver with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 170 Nm, suitable for quick driving. A handy LED light for added lighting. Two 5.0Ah batteries and a rapid charger in a Makpac case.



Technical specifications

Brushless Motor	✓
Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	0 - 3400 min ⁻¹
Max Fastening Torque Impact Drill	170 Nm
Tightening Capacity Standard Bolt	M5 - M16
Impacts per Minute (IPM)	0 - 3600 min ⁻¹
Driving Shank	1/4 "
Sound Power Level (L _{WA})	107 dB(A)
Sound Pressure Level (L _{pA})	96 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Fastening Bolt	13,0 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	1,3 - 1,6 kg
Product Dimensions (L x W x H):	126 x 79 x 238 mm

User benefits

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site

EAN 0088381823975

Link to product - www.makita.com



Related products

Standard AC

821550-0

Makpac case (2)



346317-0

Belt Hook



450128-8

Battery cover, LXT®, 14,4 – 18V



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

194250-8

Adaptor Chuck - 1/4 Hex Keyless



450128-8

Battery cover, LXT®, 14,4 – 18V



821550-0

Makpac case (2)



837670-0

MakPac (2) Inlay



B-42961

Threaded Rod Socket M6



B-42977

Threaded Rod Socket M8



B-42983

Threaded Rod Socket M10



Other

User manual

Parts drawing