

Die Grinder

GD0800C

750 W • 7 000 – 28 000 min⁻¹ • 8 mm

Efficient high-speed die grinder

A slimline, light die grinder with a 6 mm collet. Equipped with constant speed electronics and SJS technology to protect the user against kickback. Suitable for small-scale grinding, including burr removal, with the long frame offering good reach. Speed can be adjusted between 7 000 – 28 000 min⁻¹.



Technical specifications

Continuous Input Power	750 W
No load speed	7000 - 28 000 min ⁻¹
Max. Collet Capacity	8 mm
Wheel point max.	25 mm
Collar Clamping Diameter	35/43 mm
Power Supply Cord	2,5 m
Sound Pressure Level (L _{pA})	78 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	4,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Weight Without Cable (EPTA)	1,6 kg
Product Dimensions (L x W x H):	371 x 75 x 75 mm

EAN 0088381034579

Link to product - www.makitauk.com



Related products

Optional AC

192988-9

Collet cone 8 mm

193012-1

Collet cone 6 mm

193903-6

Dust cover set, 115 / 125 / 150 mm

781006-4

Spanner 13 Mm

B-52716

TCT Burr 10 x 20 x 6 mm, Standard

B-52738

TCT Burr 10 x 20 x 6 mm, Non-

B-52750

TCT Burr 10 x 20 x 6 mm, Diamond



193011-3

Collet cone 3 mm



193144-4

Collet Cone 1/8" Set with Nut



763645-2

Collet nut



781206-6

Wrench 19



B-52722

TCT Burr 10 x 20 x 6 mm, Diamond



B-52744

TCT Burr 10 x 20 x 6 mm, Standard



B-52766

TCT Burr 10 x 20 x 6 mm, Non-



Other

User manual

Parts drawing