

Blower XGT®

UB001GZ

40Vmax • 53 m/s • 13.5 m³/min

Efficient brushless blower for demanding use.

XGT® powered versatile and extremely efficient blower for construction and gardening. Equipped with a brushless motor. In Boost mode, 17N max blowing force is always available. Tool only, battery and a charger not included.



Technical specifications

Brushless Motor	✓
Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 20 000 / 23 000 min ⁻¹
Max. Air Velocity	53 / 64 m/s
Air volume	0 - 13,5 / 16 m³/min
Sound Power Level (L _{WA})	94,1 dB(A)
Sound Pressure Level (L _{pA})	83,7 dB(A)
Noise Uncertainty (K Factor)	3,1 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s²
Vibration Uncertainty (K Factor)	1,5 m/s²
Product net weight	2,4 kg
Tool weight with battery (EPTA)	3,1 - 4,5 kg
Product Dimensions (L x W x H):	917 - 1017 x 167 x

User benefits

- Max blowing force can be easily obtained by fully pulling the trigger (Boost mode)
- Compact and lightweight for single handed operation
- Lock-on button operable from either side of handle for continuous operation
- High power and less user fatigue
- The best choices for use in resorts, public places and residential areas
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381740906

Link to product - www.makita.uk.com



Related products

Standard AC

166094-6 Shoulder Belt		191L96-5 Adapter Pipe	
412758-3 End Nozzle		456957-7 Extension Nozzle	
456958-5 Flat Nozzle			

Optional AC

166094-6 Shoulder Belt		183P97-1 Extension Nozzle Set	
191C15-7 Adapter Pipe Set		191L96-5 Adapter Pipe	
197888-8 Blower Extension Nozzle		197889-6 Flat nozzle	
412758-3 End Nozzle		455915-0 Telescoping Blower Nozzle	
456957-7 Extension Nozzle		456958-5 Flat Nozzle	

Other

User manual

Parts drawing