



### Explication

Fraises HSS-E CO à chambrer 90°, DIN 1866

### Caractéristiques

Caractéristique	Valeur
Type de produit	Fraise à chambrer

## Variantes

Code article	Adapté à la dimension du filetage métrique	Diamètre de fraisage (mm)	Diamètre de la broche
<a href="#">02405029</a>	M3	6 mm	3,20 mm
<a href="#">02405030</a>	M3	6 mm	2,50 mm
<a href="#">02405031</a>	M3	6 mm	3,40 mm
<a href="#">02405037</a>	M4	8 mm	4,30 mm
<a href="#">02405038</a>	M4	8 mm	3,30 mm
<a href="#">02405039</a>	M4	8 mm	4,50 mm
<a href="#">02405041</a>	M5	10 mm	5,30 mm
<a href="#">02405042</a>	M5	10 mm	4,20 mm
<a href="#">02405043</a>	M5	10,40 mm	5,50 mm
<a href="#">02405045</a>	M6	11,50 mm	6,40 mm
<a href="#">02405046</a>	M6	11,50 mm	5 mm
<a href="#">02405047</a>	M6	12,40 mm	6,60 mm
<a href="#">02405049</a>	M8	15 mm	8,40 mm
<a href="#">02405050</a>	M8	15 mm	6,80 mm
<a href="#">02405051</a>	M8	16,40 mm	9 mm
<a href="#">02405053</a>	M10	19 mm	10,50 mm
<a href="#">02405054</a>	M10	19 mm	8,50 mm
<a href="#">02405055</a>	M10	20,40 mm	11 mm