

S.H - Douilles 1/2" 6 pans métriques



Description :

- Profil OGV® : plus de puissance et de sécurité, préserve les écrous.
- Présentation : chromée brillante.

	A [mm]	Diamètre [mm]	Diamètre D1 [mm]	longueur [mm]	Longueur L1 [mm]	Poids [g]
S.10H	10.0	22,8	15.3	36.0	7.8	50.0
S.10HPB	10.0	22,8	15.3	36.0	7.8	50.0
S.11H	11.0	22,8	16.5	36.0	9.0	50.0
S.11HPB	11.0	22,8	16.5	36.0	9.0	50.0
S.12H	12.0	22,8	17.8	36.0	9.5	50.0
S.12HPB	12.0	22,8	17.8	36.0	9.5	50.0
S.13H	13.0	22,8	18.9	36.0	10.4	50.0
S.13HPB	13.0	22,8	18.9	36.0	10.4	50.0
S.14H	14.0	22,8	20.2	36.0	10.5	55.0
S.14HPB	14.0	22,8	20.2	36.0	10.5	55.0
S.15H	15.0	22,8	21.4	36.0	12.0	55.0
S.15HPB	15.0	22,8	21.4	36.0	12.0	55.0
S.16H	16.0	21,6	22.6	36.0	12.0	55.0
S.16HPB	16.0	21,6	22.6	36.0	12.0	55.0
S.17H	17.0	23,1	24.1	36.0	13.0	65.0
S.17HPB	17.0	23,1	24.1	36.0	13.0	65.0
S.18H	18.0	23,4	25.5	36.0	13.0	70.0
S.18HPB	18.0	23,4	25.5	36.0	13.0	70.0
S.19H	19.0	24,6	26.6	36.0	14.0	75.0
S.19HPB	19.0	24,6	26.6	36.0	14.0	75.0
S.20H	20.0	25,4	27.4	36.0	14.0	80.0
S.21H	21.0	25,1	29.1	38.0	16.0	85.0
S.22H	22.0	26,4	30.4	38.0	16.5	95.0
S.22HPB	22.0	26,4	30.4	38.0	16.5	95.0
S.23H	23.0	27,6	31.6	38.0	16.5	105.0
S.23HPB	23.0	27,6	31.6	38.0	16.5	105.0
S.24H	24.0	28,7	32.7	38.0	16.5	115.0
S.24HPB	24.0	28,7	32.7	38.0	16.5	115.0
S.25H	25.0	27,7	34.1	38.0	16.5	125.0

S.26H	26.0	29	35.4	38.0	16.5	135.0
S.27H	27.0	29,2	36.6	44.0	19.0	160.0
S.28H	28.0	30,5	37.9	44.0	20.0	175.0
S.29H	29.0	31,3	38.7	44.0	20.0	190.0
S.30H	30.0	33	40.4	44.0	20.0	200.0
S.31H	31.0	34,2	41.6	44.0	20.0	205.0
S.32H	32.0	35,1	42.6	44.0	20.0	210.0
S.34H	34.0	37,5	44.9	44.0	20.0	240.0
S.8H	8.0	22,8	13.1	36.0	6.5	45.0
S.9H	9.0	22,8	13.8	36.0	6.5	50.0