

ALFRA ROTABEST® – TCT CORE DRILLS

- with Weldon shank 19.0 mm
- Internal bore: \varnothing 12 mm = 5.0 mm
 \varnothing 14 - 17 mm = 6.35 mm
 \varnothing 18 - 50 mm = 8.0 mm
- Polished section: Pre- Middle - Post cutter
- For the highest standards in cutting and lifespan.

Suitable on:

all magnetic drilling machines with Weldon shank. ALFRA-Rotabest® (Weldon), ALFRA-Rota-Quick® Quick-change system, for BDS, Bux, Ruko, Magnetor, Euroboor, Universal, Jancy, Hougen, Magtron, Promac, Rotabroach, among others.



Ø in mm cutting depth 35 mm Prod.-No.

12.0	2003012035
14.0	2003014035
15.0	2003015035
16.0	2003016035
17.0	2003017035
18.0	2003018035
19.0	2003019035
20.0	2003020035
21.0	2003021035
22.0	2003022035
23.0	2003023035
24.0	2003024035
25.0	2003025035
26.0	2003026035
27.0	2003027035
28.0	2003028035
29.0	2003029035
30.0	2003030035
31.0	2003031035
32.0	2003032035
33.0	2003033035
34.0	2003034035
35.0	2003035035

Ejector pin 1934500
for \varnothing 12 mm, 5 x 87 mm

Ejector pin 1935500
for \varnothing 14 - 17 mm, 6.35 x 87 mm


Ejector pin 2001500
for \varnothing 18 - 50 mm, 8 x 87 mm

Ø in mm cutting depth 50 mm Prod.-No.

14.0	2003014050
15.0	2003015050
16.0	2003016050
17.0	2003017050
18.0	2003018050
19.0	2003019050
20.0	2003020050
21.0	2003021050
22.0	2003022050
23.0	2003023050
24.0	2003024050
25.0	2003025050
26.0	2003026050
27.0	2003027050
28.0	2003028050
29.0	2003029050
30.0	2003030050
31.0	2003031050
32.0	2003032050
33.0	2003033050
34.0	2003034050
35.0	2003035050
36.0	2003036050
37.0	2003037050
38.0	2003038050
39.0	2003039050
40.0	2003040050
41.0	2003041050
42.0	2003042050
43.0	2003043050
44.0	2003044050
45.0	2003045050
46.0	2003046050
47.0	2003047050
48.0	2003048050
49.0	2003049050
50.0	2003050050

Ejector pin 1950500
for \varnothing 14 - 17 mm, 6.35 x 102 mm

Ejector pin 2001501
for \varnothing 18 - 50 mm, 8 x 102 mm



ALFRA „Chip-Breaker System“

- 1 Pre-cutter
- 2 Middle-cutter
- 3 Post-cutter

On request with shank for NITTO One-Touch