

# RATCHETS

## CP825T ★



### SMALL & DURABLE


#### FEATURES

- Progressive tease throttle
- Small ratchet, only 6.5" (165 mm) long
- Convenient forward and reverse button

#### BENEFITS

- Ratchets for General Maintenance
- Ideal for tight access applications
- Compact and lightweight

## CP828H ★



### CP828

Same features as CP828H with 3/8" Square Drive

### DURABLE

#### FEATURES

- Durable aluminum alloy design
- Features CP's patented TriSpring anti-slip head design
- Grease fitting on the reverse lever

#### BENEFITS

- General maintenance and excellent durability
- Great power up to 50 ft.lbs (70 Nm)
- General maintenance and excellent durability



## CP7830HQ ★



### CP7830Q

Same features as CP7830HQ with 3/8" square drive

### POWERFUL, COMFORTABLE & DURABLE

#### FEATURES

- Adjustable side exhaust, low noise
- Progressive tease throttle
- Highest torque on the market: 90 ft.lbs (122 Nm)

#### BENEFITS

- Ratchet for General Maintenance applications
- High torque & durable
- Light weight and well balanced tool



See accessories and dimensions on pages 29-31



| MODEL    | PART NUMBER  | DRIVE | FREE SPEED |       | WORKING TORQUE (FW) |    | MAX TORQUE (FW) |     | NET WEIGHT |     | LENGTH |      | AIR CONS @FREE SPEED |     | VIBRATION LEVEL ISO 28927 (M/S2) |    | SOUND PRESS.      | SOUND POWER | AIR INLET |
|----------|--------------|-------|------------|-------|---------------------|----|-----------------|-----|------------|-----|--------|------|----------------------|-----|----------------------------------|----|-------------------|-------------|-----------|
|          |              |       | in.        | rpm   | ft.lb               | Nm | ft.lb           | Nm  | lb         | kg  | in.    | mm   | cfm                  | l/s | a                                | k  | ISO 15744 - db(a) | in.         |           |
| CP7830HQ | 894 107 8308 | 1/2   | 190        | 10-90 | 13-122              | 90 | 122             | 2.7 | 1.2        | 12  | 305    | 21.0 | 8.7                  | 4.1 | 1.4                              | 85 | 96                | 1/4         |           |
| CP7830Q  | 894 107 8306 | 3/8   | 190        | 10-90 | 13-122              | 90 | 122             | 2.7 | 1.2        | 12  | 305    | 21.0 | 8.7                  | 4.1 | 1.4                              | 85 | 96                | 1/4         |           |
| CP825T   | T023190      | 3/8   | 200        | 5-15  | 7-21                | 15 | 21              | 1.9 | 0.9        | 6.5 | 165    | 11.0 | 5.1                  | 3   | 1.2                              | 87 | 98                | 1/4         |           |
| CP828    | T022708      | 3/8   | 150        | 10-50 | 13-70               | 50 | 70              | 2.4 | 1.1        | 10  | 254    | 15.0 | 7.1                  | 3.2 | 1.3                              | 97 | 108               | 1/4         |           |
| CP828H   | T022970      | 1/2   | 150        | 10-50 | 13-70               | 50 | 70              | 2.4 | 1.1        | 10  | 254    | 15.0 | 7.1                  | 3.2 | 1.3                              | 97 | 108               | 1/4         |           |

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.