


AT.VE - Tot 1000 Volt geïsoleerde PROTWIST® schroevendraaiers voor sleufschroeven



Description:

- Bi-material grip resists to impacts, abrasion, and chemicals.[nl]
- New softer handle material for improved comfort.[nl]
- Fillet blade: 6.5 --> 12 mm.[nl]
- 1,000 Volt sheathed round blade.[nl]
- New chemical resistant handle with "power" channel for higher torque transfer.[nl]
- Milled blade: --> 5.5 mm included.[nl]
- For your safety, each screwdriver is tested individually at 10,000 volts for 10 seconds, at the end of the manufacturing cycle.[nl]

	a [mm]	A [mm]	A [mm]	Diameter [mm]	Lengte [mm]	Lengte L1 [mm]	Lengte [mm]	Lengte L3 [mm]	Dikte [mm]	Gewicht [g]
AT10X200VE	10.0	10.0		40.0	325.0	200.0	125.0	18.0	1.6	240.0
AT12X250VE	12.0	12.0		40.0	375.0	250.0	125.0	18.0	2.0	360.0
AT2.5X50VE	2.5	2.5		25.0	153.0	50.0	103.0	18.0	0.4	30.0
AT2.5X50VEPB		2.5								
AT2.5X75VE	2.5	2.5		25.0	178.0	75.0	103.0	18.0	0.4	32.0
AT2X75VE	2.0	2.0		19.0	170.0	40.0	95.0	18.0	0.4	23.0
AT3.5X100VE	3.5	3.5		25.0	204.0	100.0	104.0	18.0	0.6	44.0
AT3.5X100VEPB		3.5								
AT3.5X75VE	3.5	3.5		25.0	179.0	75.0	104.0	18.0	0.6	42.0
AT3.5X75VEPB		3.5								
AT3X100VE	3.0	3.0		25.0	202.0	100.0	103.0	18.0	0.5	39.0
AT3X75VE	3.0	3.0		25.0	178.0	75.0	103.0	18.0	0.5	38.0
AT4X100VE	4.0	4.0		30.0	210.0	100.0	110.0	18.0	0.8	48.0
AT4X100VEPB		4.0								
AT4X150VE	4.0	4.0		30.0	260.0	150.0	110.0	18.0	0.8	53.0
AT4X150VEPB		4.0								
AT5.5X125VE	5.5	5.5		30.0	235.0	125.0	110.0	18.0	1.0	88.0
AT5.5X150VE	5.5	5.5		30.0	260.0	150.0	110.0	18.0	1.0	92.0
AT5.5X150VEPB		5.5								
AT5.5X200VE	5.5	5.5		30.0	310.0	200.0	110.0	18.0	1.0	106.0
AT6.5X150VE	6.5	6.5		36.0	270.0	150.0	120.0	18.0	1.2	120.0
AT6.5X200VE	6.5	6.5		36.0	320.0	200.0	120.0	18.0	1.2	170.0
AT6.5X200VEPB		6.5								
AT8X150VE	8.0	8.0		40.0	275.0	150.0	125.0	18.0	1.2	160.0
AT8X200VE	8.0	8.0		40.0	325.0	200.0	125.0	18.0	1.2	180.0
AT8X200VEPB		8.0								