


ATX - PROTWIST® schroevendraaiers voor Torx® schroeven



Description:

- Laser Marking - gives virtually Permanent Marking.[nl]
- Handle 'Channel' - +10% Torque.[nl]
- Inline Hardening Process – +100% Tip Life and +100% Bar Strength. [nl]
- Compliant with Torx® specifications.[nl]
- Handle Material - Softer for more Comfort and still Chemical Resistant.[nl]
- CNC tip machining - gives better Screw Fit increasing Torque Transfer and Reducing Wear.[nl]
- Blade " tri-coating " treatment (Zinc-Nickel-Chromium) - 4x Corrosion Resistance.[nl]

	a [mm]	A [mm]	A [°]	Diameter [mm]	Diameter D1 [mm]	Length L1 [mm]	Length [mm]	Length [mm]	Gewicht [g]	Torx Tip Aantal ["]
ATX10X75	2.74	2.74			3.0	75.0	184.0	109.0	50.0	T10
ATX10X75PB		2.74			3.0	75.0	184.0	109.0	50.0	T10
ATX15X75	3.26	3.26			3.5	75.0	184.0	109.0	61.0	T15
ATX15X75PB		3.26			3.5	75.0	184.0	109.0	61.0	T15
ATX20X100	3.84	3.84			4.0	100.0	220.0	120.0	67.0	T20
ATX20X100PB		3.84			4.0	100.0	220.0	120.0	67.0	T20
ATX20X150	3.84	3.84		36.0	4.0	150.0	270.0	120.0	73.0	T20
ATX25X100	4.4	4.4			5.0	100.0	220.0	120.0	113.0	T25
ATX25X100PB		4.4			5.0	100.0	220.0	120.0	113.0	T25
ATX27X100	4.96	4.96			5.5	100.0	220.0	120.0	113.0	T27
ATX30X125	5.49	5.49			6.0	125.0	245.0	120.0	126.0	T30
ATX30X125PB		5.49			6.0	125.0	245.0	120.0	126.0	T30
ATX40X150	6.6	6.6		40.0	7.0	150.0	275.0	125.0	173.0	T40
ATX6X50	1.65	1.65			2.5	50.0	144.0	94.0	20.0	T6
ATX7X50	1.97	1.97			2.5	50.0	144.0	94.0	20.0	T7
ATX8X50	2.3	2.3			2.5	50.0	153.0	103.0	35.0	T8
ATX9X75	2.48	2.48			3.0	75.0	178.0	103.0	45.0	T9