

Spark plug socket

Square, hollow 10 mm (3/8 inch) · Outside hexagon profile · 16 mm · 5/8 "

Article no.: 880AKF
EAN: 4000896040131

Product information

Application:

Installing and removing spark plugs (s 16 mm = 5/8")

- The fixing clamp reduces the risk of insulator damage
- **Fixing clamp** to hold the spark plug
- Long design
- American dimensions
- Surface: chrome-plated, polished
- Made in Germany
- Drive: Square, hollow 10 mm (3/8 inch)
- Output: Outside hexagon profile
- Wrench size: 16 mm · 5/8 "
- Dimensions / length: 64 mm
- Diameter d1 (output side): 21.6 mm
- Diameter d2 (drive side): 21.6 mm
- Net weight: 0.1 kg
- For manual operation

Stainless and insensitive to heat

Largest possible clearance of insulator

6 spring elements – firm hold of the spark plug

Damping of transverse motion



TECHNICAL DATA

- **Output:** ●
- **Manual / impact operation:** For manual operation
- **Drive:** 10^{3/8}
- **American dimensions:** American dimensions
- **Diameter d2 (drive side):** 21.6 mm
- **Depth:** 10 mm
- **Diameter d1 (output side):** 21.6 mm
- **Surface:** chrome-plated, polished
- **Dimensions / length:** 64 mm
- **Wrench size:** 16 mm · 5/8 "

