



Impact wrench · extra short

Maximum loosening torque: 1200 Nm · Square, solid 12.5 mm (1/2 inch) · Single hammer striking mechanism

Article no.: 9012M-1

EAN: 4000896218356

Product information

Application:

Ultra compact design optimised for work in confined spaces

- Maximum loosening torque: 1200 Nm
- One-hand operation for right and left-handed operators
- Exhaust air is guided through the handle downwards
- Reduced vibrations
- Easy handling
- **Extra short – only 80 mm**
- Single hammer striking mechanism
- Air connection inlet: Inside thread 12.91 mm (1/4")
- Coupler plug: Nominal size 7.2 (included)
- Recommended torque: 610 Nm
- Hose diameter (recommended): 10 mm
- Working pressure (bar): 6.3
- Sound power level: 103.2 db(A) Lp W
- Vibration acceleration: 13.49 m/s²
- Loosening torque (max) determined with screw size M: 16
- Forward and reverse: three-stage (forward), single-stage (reverse)
- Cold insulated handle
- Output: Square, solid 12.5 mm (1/2 inch)
- Dimensions / length: 80 mm
- Net weight: 1.27 kg
- Tightening torque max.: 678 Nm
- Maximum loosening torque: 1200 Nm
- Sound pressure level: 92.2 dB(A) Lp A
- Revolutions per minute: 8800
- Air requirement: 127.4 l/min (2.1 l/sec)





TECHNICAL DATA

- **Output:** 128 1/2
- **Handle:** Cold insulated handle
- **Tightening torque max.:** 678 Nm
- **Sound power level (at working pressure):** 103.2 db(A) Lp W
- **Forward/reverse:** three-stage (forward), single-stage (reverse)
- **Max. loosening torque:** 1200 Nm
- **Recommended torque:** 610 Nm
- **Loosening torque (max) determined with screw size M:** 16 M
- **Striking mechanism (type):** Single hammer striking mechanism
- **Air requirement [l/min]:** 127.4 l/min
- **Sound pressure level (at working pressure):** 92.2 dB(A) Lp A
- **Dimensions / length:** 80 mm

