

ANTI-SEIZE PASTES

TM 900S

COPPER

Copper-based assembly paste for surface treatment and lubrication. Specifically designed to treat: tools, axles, rollers, slow-moving parts and all parts that will need dismantling. Recommended for pouring nozzles in steelworks. Electrical and thermal conductor.



600



■ copper
T°: -40 to +1100°C

- 4600A4 650 ml aerosol
- 3600B4 250 ml tin with brush
- 3600C4 400 g cartridge
- 3600B7 1 kg tin
- 360002 25 kg drum
- 3600U1 180 kg drum



HT900

COPPER

Anti-seize product formulated to leave a thin lubricating layer. For threaded parts that will need to be assembled and dismantled after being exposed to very high temperatures. Refineries, dyeworks, oven, marine...

637



■ copper
T°: -40 to +1100°C

- 3637T4 200 g tube
- 3637B6 500 g tin
- 3637B7 1 kg tin
- 3637S1 5 kg tub
- 3637U2 200 kg drum



HTCU

COPPER

Copper paste specifically designed for the rail sector providing corrosion protection for threaded assemblies on carriages, engines and rail tracks.

647



■ copper
T°: -40 to 1100°C

- 3647T4 200 g tube
- 3647B7SNCF 1 kg tin
- 364704 50 kg drum



LUBRICATE



THERMALLY CONDUCTIVE PASTES

PC 195

WHITE

Provides sealing and thermal transfer of heat energy while preserving the static and dimensional stability of protected devices. Alternators, starters, electrical and electromechanical devices.

641



■ white
T°: -40 to +200°C
Silicone-based

- 3641E4 30 ml syringe
- 3641C3 300 g cartridge
- 3641B7 1 kg tin
- 364102 25 kg drum
- 364104 50 kg drum



L 362

HIGH EFFICIENCY

Heat-conducting assembly and sealing paste. Any domain where thermal conductivity between two surfaces must be improved, heat energy transfer must be facilitated and the transfer surface area must be increased. Alternators, starters, probes, electrical and electromechanical devices, heat sensors etc. Assembly, lubrication, sealing etc.

6412



■ black
T°: -40 to +180°C
Thermal conductivity:
0.8 W/m.K
NLGI Grade: 3

- 36412C3 300 g cartridge
- 3641202 25 kg drum



CT 10

MULTI-PURPOSE LITHIUM GREASE

EP2 multi-purpose lithium grease suitable for general lubrication, maintenance and the automotive industry in applications that are not overly demanding. Lubrication of chassis, farm equipment, civil engineering equipment, etc.

677

■ light amber
T°: -25 to +130°C
NLGI Grade: 2
4-ball EP:
250 kg
DN Factor:
350 000

- 3677C4 400 g cartridge
- 3677B7 1 kg tin
- 367704 50 kg drum
- 3677U1 180 kg drum



CT 4

MOS2 GREASE

Greasing under very heavy loads, effectively combats wear thanks to its concentration of high quality MoS2. Mechanical construction, automotive industry, arms industry etc. Safe lubrication of bearings.

608



■ grey/black
T°: -30 to +165°C
NLGI Grade: 2
4-ball EP:
315 kg
DN Factor:
350 000

- 4608A4 650 ml aerosol
- 3608T4 200 g tube
- 3608C4 400 g cartridge
- 3608B7 1 kg tin
- 360802 25 kg drum
- 360804 50 kg drum

