

STANDARD GREASES

CT 12 G

GRAPHITE GREASE

Greasing under very heavy load, fights effectively against wear thanks to the presence of micronised graphite. Has an extremely low coefficient of friction. Humid conditions and mechanisms subject to shocks. Ideal for applications in the automotive industry, trucks and general industry.

625

■ black
T°: -30 to +130°C
NLGI Grade: 2
4-ball EP:
315 kg
DN Factor:
350 000



3625C4	400 g cartridge
3625B7	1 kg tin
3625O2	25 kg drum

CT 14

MULTI-PURPOSE, LITHIUM-BASED

Multi-purpose EP2 grease for bearings and mechanisms subject to heavy loads. Ideal for industrial applications, automobiles, trucks etc.



602



■ light amber
T°: -30 to 165°C
NLGI Grade: 2
4-ball EP:
315 kg
DN Factor:
350 000

4602A4	650 ml aerosol
3602T3	100 g tube
3602C4	400 g cartridge
3602CL	Lube shuttle 400 g
3602B7	1 kg tin
3602S1	5 kg tub
3602O2	25 kg drum
3602O4	50 kg drum



CT 140

FLUID GREASE FOR CENTRALISED LUBRICATION

Multi-purpose fluid EP grease for bearings and mechanisms subject to heavy loads and requiring lubrication via a centralised system. Reinforced protection against extreme pressure and wear. Ideal for applications in the car manufacturing, HGV, and industrial sectors.

680

■ amber
T°: -40 to +165°C
NLGI Grade: 0-00
4-ball EP:
315 kg
DN Factor:
350 000



3680S1	5 kg tub
3680O2	25 kg drum
3680O4	50 kg drum
3680U1	180 kg drum

CT 143

LUBRICATION/SEALING

Valves and taps can be sealed and lubricated in a single operation thanks to the thick, paste like consistency of this product. Multipurpose EP3 grease for bearings and other mechanisms that require a thick grease. Ideal for industrial applications, cars and trucks.

743

■ amber
T°: -30 to +165°C
Drop point:
180
NLGI Grade: 3
4-ball EP:
315 kg
DN Factor:
350 000

3743B7	1 kg tin
3743O4	50 kg drum

CT FLON

PTFE GREASE

Teflon® grease for lubrication under heavy load. Lubricating effect reinforced by Teflon, noise decrease, chemically inert. Ideal for lubrication on plastics. Good water resistance.

607

■ light beige
T°: -20 to 140°C
4-ball EP:
315 kg
DN Factor:
350 000



4607A4	650 ml aerosol
3607C4	400 g cartridge
3607B7	1 kg tin
3607S1	5 kg tub

GRAISSE UNIVERSELLE

CLEAN GREASE

Adhesive, non-drip, odourless, corrosion inhibiting grease, compatible with all materials. Moisture resistant. For doors, locks, hinges, runners, chains, rubber or plastic parts, household appliances, tools etc.

635

■ colourless
T°: -30 to +150°C
Drop point: none
DN Factor:
350 000



4635A4	650 ml aerosol
--------	----------------

SPECIAL GREASES

ENG CB 612

CABLES/GEARS

Soft grease for cables, gear reducers, bevel and hypoid gears, tooth couplings. Quarries, public works, crushers, ski resorts etc. Excellent anti-wear properties, considerably lengthens the lifespan of gear teeth.

612

■ light brown
T°: -50 to +220°C
4-ball EP:
780 kg
NLGI Grade: 0



4612A4	650 ml aerosol
3612C4	400 g cartridge
3612S1	5 kg tub
3612O5	50 kg drum
3612U1	180 kg drum

CT BIO

BIODEGRADABLE

Multi-purpose grease for outdoor use: locks, barriers, agriculture, forest management, cable cars, public works, port areas etc. Excellent water and storm water resistance.



687

■ green
T°: -25 to +145°C
4-ball EP:
315 kg
DN Factor:
500 000



3687C4	400 g cartridge
3687O2	25 kg drum

PENETRATE & RELEASE

CLEAN

USE



LUBRICATE

ASSEMBLE

PROTECT