

SPECIAL BONDING

THERMIQUE PMUC 418

HIGH-TEMPERATURE PUTTY GLUE

Silicone-free putty glue. Jointing, bonding and sealing, specifically formulated to withstand very high temperatures. Asbestos-free. Hardens completely, to the very centre. Do not use in contact with water. For cracks or holes filling-in, over metal, stones or concrete... Stoves, boilers, furnaces, open fireplaces, probes, car exhaust pipe fittings.



■ Anthracite grey
thick paste

T°: -40 to +1200°C

Thickness: 5 to 15 mm

Shore A hardness: 70 to 90

PMUC: 17-0385



1418C3 310 ml cartridge

COLLE REPOSITIONNABLE 477

POST-IT TYPE GLUE IN AEROSOL

Immediate adhesion. Posters or labels can be repositioned easily up to several weeks after gluing. For gluing light materials: photos, films, cork, foam board, decorations.

■ beige

Setting time: immediate

Consumption: 1 aerosol = 7 m²



4477A4 650 ml aerosol

NEOPRENE 400

MULTI-PURPOSE CONTACT ADHESIVE

Instant setting on rubber, leather, fabric, cork, metals, laminates. Flexible, high efficiency. Very high resistance to pull out, excellent resistance to moisture. Applied to both surfaces (150 ml/m² per side).

■ beige

Setting time: 5 to 15 mn

Max T°: +90°C

Resistance to peeling: 15 kg/cm²



4400A4 650 ml aerosol

1400T3 100 ml tube

1400B7 1 l tin

1400S1 5 l bucket

ORASEAL 4000

NEW

FLEXIBLE ADHESIVE

Adhesive sealant with air and water between metallic and plastics parts :
Cladding stonework, facades, metal bracings. Car body. Elements of cold rooms. Corrosion inhibitor. Horizontal leak and bonding in the car industry. Stick on glass, cement, aluminium, steel, ...

347

1347C6 600 ml cartridge

MOUSSE PU 474

INSULATING FIRE-RETARDANT FOAM

80% closed cell expanding foam for thermal and acoustic insulation and caulking. Gas, smoke, flame and water tight. Doors mounting, windows and other articles designed to slow down fire propagation, including in high schools, local authorities and hospitals. Must be applied onto wet surfaces.

■ grey

very sticky foam

T°: -60 to +100 °C

Fire resistance: 120 mn

Coverage: 20 to 35 litres/aerosol

4474A6 1000 ml aerosol

ADHERENT COURROIES 953

STOPS DRIVE BELTS FROM SLIPPING

Triples belt adherence for rubber, leather, canvas, or composite. Prevents belts from hardening while eliminating power loss. Treated belts wear more slowly and transmit power more effectively. Helps position pre-cut gaskets onto crankcases. For treating conveyor belts to provide better grip.

■ yellow

liquid

Max T°: +80°C



4953A4 650 ml aerosol

PENETRATE & RELEASE

CLEAN

USE

LUBRICATE



ASSEMBLE

PROTECT