

#### BASIC




FC 800040

#### PRO-815



FC 815060



Uitgerust met aluminium 90°  
winkelhoak.  
Équipé d'une équerre à 90°  
en aluminium.

#### PRO-815 LAZER



Gebruikt met Ø 18 mm snijwiel.  
Utilisé avec une molette de Ø  
18 mm.



#### KENMERKEN CARACTÉRISTIQUES

FC 800040 BASIC	400 mm	8 mm	282 x 282 mm	2,500 kg
FC 815047 (PRO-815 / 470 mm)	470 mm	12 mm	332 x 332 mm	5,350 kg
FC 815060 (PRO-815 / 600 mm)	600 mm	12 mm	424 x 424 mm	6,250 kg
FC 815085 (PRO-815 / 850 mm)	850 mm	12 mm	601 x 601 mm	7,800 kg
FC 815093 (PRO-815 / 850 mm + laser)	850 mm	12 mm	601 x 601 mm	8,450 kg

code						min.
------	--	--	--	--	--	------

#### BASIC

FC 800040		5420000062047	BASIC - 400 mm	2,500 kg	128	1	1
Vervangsnijwiel SET - Ø 15 x 6 x 2 mm • Molette de rechange en SET - Ø 15 x 6 x 2 mm							
FC 800141		5420000062054	BASIC	0,016 kg	-	1	1

#### PRO-815

FC 815047		5420000062061	PRO-815 - 470 mm	5,950 kg	36	1	1
FC 815060		5420000062078	PRO-815 - 600 mm	6,950 kg	66	4	1
FC 815085		5420000062085	PRO-815 - 850 mm	8,666 kg	44	1	1
Vervangsnijwiel SET - Ø 18 x 6 x 1,5 mm • Molette de rechange en SET - Ø 18 x 6 x 1,5 mm							
FC 815191		5420000062092	PRO-815	0,018 kg	-	1	1

#### PRO-815 LAZER

FC 815093		5420000062191	PRO-815 - 850 mm	9,000 kg	45	3	1
Vervangsnijwiel SET - Ø 18 x 6 x 1,5 mm • Molette de rechange en SET - Ø 18 x 6 x 1,5 mm							
FC 815191		5420000062092	PRO-815	0,018 kg	-	1	1

