







SUPER DUCT

**SUPER DUCT
HEAVY DUTY
"ALL WEATHER"**

SUPER METAL

40 micron

code								min.
Duct TAPE ECO (ST 101)				mm x m				
ST 4471101	vrac	8714828010067	●	48 x 50	302 gr	756	36	36
Super Duct (ST 401)								
ST 4471960	vrac	8714828000754	●	50 x 50	492 gr	1152	24	24
ST 4471890	vrac	8714828000778	●	50 x 50	506 gr	1152	24	24
ST 4471900	vrac	8714828000761	●	50 x 50	498 gr	1152	24	24
Super Duct Heavy Duty (ST 501)								
ST 4474241	vrac	8714828001362	●	50 x 50	650 gr	432	24	24
Super Metal - 40 micron								
ST 9105050	vrac	5420000025158		alu - 40 micron	50 x 50	453 gr	864	24
ST 9107075	vrac	5420000025165		alu - 40 micron	75 x 50	759 gr	960	16
ST 9108120	vrac	5420000025172		alu - 40 micron	100 x 50	986 gr	720	12

	SUPER DUCT ECO	SUPER DUCT	SUPER DUCT HEAVY DUTY	SUPER METAL
Temperatuursbestendigheid <i>Résistance thermique</i>	-10°C → 75°C	-15°C → 60°C	-25°C → 80°C	-20°C → 120°C
Kleefkracht <i>Adhésivité</i>	sterk <i>forte</i>	zeer sterk <i>très forte</i>	zeer sterk <i>très forte</i>	goed <i>bonne</i>
Drager <i>Support</i>	Polyester weefsel <i>Fibre polyester</i>	Polyester weefsel <i>Fibre polyester</i>	PE vezelbekleding <i>couvert fibre PE</i>	ALU
Kleeflaag <i>Adhésif</i>	synthetisch rubber <i>caoutchouc synth.</i>	Hotmelt	synthetisch rubber <i>caoutchouc synth.</i>	acrylaat <i>acrylique</i>
Rekbaarheid <i>Elasticité</i>	-	-	-	-