

93-...

Hexagonal/bi-hexagonal polished open socket wrenches in mm


"Right side opening 6""", angled opening 12""

standard hallmark

high tightening torque

""classic"" finishing: polish satin"

CLASSIC



Normes : DIN ISO 1711-1, DIN ISO 691,
ISO 1711-1, ISO 2236, ISO 691, NF ISO
1711-1, NF ISO 2236, NF ISO 691

reference	A mm	B mm	D mm	H mm	L mm	P mm	P1 mm	Weight g
93-6	6		11	17	97	8	23	30
93-7	7		11	17	97	8	23	35
93-8	8		14	22	119	10	28	50
93-9	9		14	22	119	10	28	55
93-10	10	8	16	25	133	11	34	100
93-11	11	8	16	25	133	11	34	100
93-12	12	9		30	144	13	36	120
93-13	13	9		30	144	13	36	120
93-14	14		21	34	165	15	43	185
93-15	15		21	34	165	15	43	185
93-16	16		24	38	187	17	52	280
93-17	17		24	38	187	17	52	280
93-18	18	14		45	198	20	57	355
93-19	19	14		45	198	20	57	355
93-20	20	15	29	48	210	22	60	400
93-21	21	15	29	48	210	22	60	400

PRODUCT SHEET

93-22	22	17	32	54	231	24	66	540
93-23	23	17	32	54	231	24	66	540
93-24	24	17	34	57	237	26	66	580
93-25	25	17	34	57	237	26	66	570
93-26	26	21		60	258	28	74	770
93-27	27	21		60	258	28	74	770
93-28	28	21		62	268	30	76	860
93-29	29	21		62	268	30	76	860
93-30	30	24	41	66	292		83	1220
93-31	31	24	41	66	292		83	1220
93-32	32	24	44	68	308	33	83	1230