

94-...

Hexagonal/hexagonal satin finish open socket wrenches


"6""opening

standard hallmark

hight tightening torque

""classic""finishing:polish satin"

CLASSIC



Normes : DIN ISO 1711-1, DIN ISO 691,
ISO 1711-1, ISO 2236, ISO 691, NF ISO
1711-1, NF ISO 2236, NF ISO 691

reference	A mm	B mm	D mm	H mm	L mm	P mm	P1 mm	Weight g
94-5	5		9	13	86	6	15	25
94-5,5			9	13	86	6	15	25
94-6	6		11	17	97	8	23	30
94-7	7		11	17	97	8	23	35
94-8	8		14	22	119	10	28	50
94-9	9		14	22	119	10	28	55
94-10	10	8	16	25	133	11	34	100
94-11	11	8	16	25	133	11	34	100
94-12	12			30	144	13	36	120
94-13	13	9		30	144	13	36	120
94-14	14		21	34	165	15	43	185
94-15	15		21	34	165	15	43	185
94-16	16		24	38	187	17	52	280
94-17	17		24	38	187	17	52	280
94-18	18	14		45	198	20	57	355
94-19	19	14		45	198	20	57	355

PRODUCT SHEET

94-20	20	15	29	48	210	22	60	400
94-21	21	15	29	48	210	22	60	400
94-22	22	17	32	54	231	24	66	540
94-23	23	17	32	54	231	24	66	540
94-24	24	17	34	57	237	26	66	580
94-25	25	17	34	57	237	26	66	570
94-26	26	21		60	258	28	74	770
94-27	27	21		60	258	28	74	770
94-28	28	21		62	268	30	76	860
94-29	29	21		62	268	30	76	860
94-30	30	24	41	66	292		83	1220
94-31	31	24	41	66	292		83	1220
94-32	32	24	44	68	308	33	83	1230