

TEROSON VR 120

October 2017

PRODUCT DESCRIPTION

Technology	Cleaner and Protector for Plastics
Product Type	Silicon Oil

TEROSON VR 120 is a silicon oil-based cleaning and restoring agent for plastic components in motor vehicles. The product contains deodorizing and anti-static components and gives plastic parts a fresh silky sheen.

Application Areas:

TEROSON VR 120 is suitable for the rejuvenation of plastic components in the interiors of cars. The product can also be used to treat leather, simulated leather and polished wood.

TECHNICAL DATA

(Typical Test Results)

Colour	colorless, transparent
Odour	scented
Consistency	thin liquid
Density	~0.76 g/cm ³ (full contents)
Solids	~6 %

PRELIMINARY STATEMENT

Prior to use it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application:

The product is sprayed onto the desired area by pressing the spray button (hold can upright during use).

The sprayed surface should be rubbed with a clean, dry cloth immediately after spraying.

TEROSON VR 120 should not be sprayed on windows, steering wheels or seats.

A good method of using the product in areas close to such critical items is to spray the product onto a cloth and then wipe the surfaces concerned.

Caution:

Although most automotive paints and interior plastics have excellent solvent resistance, it is recommended to perform a compatibility test prior to application, in order to avoid damage to the paint or the plastic surface.

Storage:

Frost sensitive	no
Recommended storage temperature	10 to 25 °C

Packaging:

Spray can 300 mL

Classification:

Please refer to the corresponding **Safety Data Sheets** for details on:

Hazardous Information

Transport Regulations

Safety Regulations

Disclaimer**Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.0